



SAFETY DATA SHEET TIN ALKALINE

1. Identification

Product identifier

Product name TIN ALKALINE

Product number 2090

Recommended use of the chemical and restrictions on use

Application Industrial Use

Details of the supplier of the safety data sheet

Supplier SIFCO Applied Surface Concepts
5708 E. Schaaf Road
Independence, Ohio 44131
U.S.A.
Tel.: +1 216-524-0099
Fax: +1 216-524-6331
E-Mail: info@sifcoasc.com

Emergency telephone number

Emergency telephone CHEMTREC (United States) (800) 424-9300; CHEMTREC (International) +1 703-527-3887

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Skin Corr. 1B - H314 Eye Dam. 1 - H318 Resp. Sens. 1 - H334 Skin Sens. 1 - H317 Muta. 2 - H341 STOT RE 2 - H373

Environmental hazards Aquatic Chronic 2 - H411

Label elements

Pictogram



Signal word

Danger

Hazard statements

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H341 Suspected of causing genetic defects.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

TIN ALKALINE

Precautionary statements

P260 Do not breathe vapor/ spray.
P264 Wash contaminated skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P284 [In case of inadequate ventilation] wear respiratory protection.
P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501 Dispose of contents/ container in accordance with national regulations.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P270 Do not eat, drink or smoke when using this product.
P301+P310 If swallowed: Immediately call a poison center/ doctor.
P302+P352 If on skin: Wash with plenty of water.

Contains

TIN(II) SULPHATE, ETHYLENEDIAMINE

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

AMMONIUM TARTRATE CAS number: 14307-43-8	25-30%
Classification Not Classified	
TIN(II) SULPHATE CAS number: 7488-55-3 M factor (Acute) = 1 M factor (Chronic) = 1	10-15%
Classification Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Muta. 2 - H341 STOT SE 3 - H335 STOT RE 2 - H373 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	

TIN ALKALINE

ETHYLENEDIAMINE	5-10%
CAS number: 107-15-3	
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Resp. Sens. 1 - H334 Skin Sens. 1 - H317	
AMMONIUM SULPHATE	<1%
CAS number: 7783-20-2	
Classification Not Classified	

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Get medical attention.
Ingestion	Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
Skin Contact	Remove contaminated clothing immediately and wash skin with soap and water. Continue to rinse for at least 15 minutes and get medical attention.
Eye contact	Remove affected person from source of contamination. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention.

Most important symptoms and effects, both acute and delayed

Inhalation	Coughing, chest tightness, feeling of chest pressure.
Ingestion	May cause chemical burns in mouth and throat. May cause stomach pain or vomiting.
Skin contact	May cause serious chemical burns to the skin.
Eye contact	Causes severe burns. May cause serious eye damage.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations.
-----------------------------	------------------------------

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

Special hazards arising from the substance or mixture

Specific hazards Toxic and corrosive gases or vapors.

Advice for firefighters

TIN ALKALINE

Protective actions during firefighting Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

Special protective equipment for firefighters Use protective equipment appropriate for surrounding materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of vapors. Provide adequate general and local exhaust ventilation.

Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses. Collect and dispose of spillage as indicated in Section 13. Wash thoroughly after dealing with a spillage.

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Avoid inhalation of vapors and spray/mists. Provide adequate general and local exhaust ventilation.

Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Protect from freezing and direct sunlight.

Storage class Toxic storage. Corrosive storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

ETHYLENEDIAMINE

Long-term exposure limit (8-hour TWA): OSHA 10 ppm 25 mg/m³

OSHA = Occupational Safety and Health Administration.

Exposure controls

Protective equipment



TIN ALKALINE

Appropriate engineering controls	As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapor or mist.
Eye/face protection	Tight-fitting safety glasses.
Hand protection	It is recommended that chemical-resistant, impervious gloves are worn. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. It is recommended that gloves are made of the following material: Nitrile rubber.
Other skin and body protection	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
Hygiene measures	Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Clear, yellowish liquid.
Odor	Odorless.
pH	pH (diluted solution): 7.0-7.4
Flash point	Not applicable.
Evaporation rate	<1
Relative density	1.223-1.263
Other information	Not available.
Volatile organic compound	This product contains a maximum VOC content of EDA 108 g/l.

10. Stability and reactivity

Reactivity	Acid-reactive materials.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	Acid-reactive materials.
Conditions to avoid	Avoid excessive heat for prolonged periods of time.
Materials to avoid	Acids - oxidizing.
Hazardous decomposition products	None at ambient temperatures.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

TIN ALKALINE

ATE oral (mg/kg) 5,747.13

Acute toxicity - dermal

ATE dermal (mg/kg) 12,643.68

Acute toxicity - inhalation

ATE inhalation (dusts/mists mg/l) 11.28

Inhalation Vapor from this product may be hazardous by inhalation.

Ingestion Toxic if swallowed. Causes severe burns. May cause chemical burns in mouth, esophagus and stomach.

Skin Contact May cause serious chemical burns to the skin. May cause sensitization or allergic reactions in sensitive individuals.

Eye contact Causes serious eye damage. Immediate first aid is imperative.

Acute and chronic health hazards Causes severe burns. May cause cancer.

Route of entry Ingestion Inhalation Skin and/or eye contact

Toxicological information on ingredients.**TIN(II) SULPHATE****Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg) 2.207

Species Rat

Acute toxicity - inhalation

ATE inhalation (dusts/mists mg/l) 1.5

ETHYLENEDIAMINE**Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg) 1,200.0

Species Rat

ATE oral (mg/kg) 500.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 560.0

Species Rabbit

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ dust/mist mg/l) 14.7

TIN ALKALINE

Species	Rat
ATE inhalation (vapours mg/l)	11.0

AMMONIUM SULPHATE**Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg)	4,250.0
--	---------

Species	Rat
----------------	-----

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg)	2,000.0
--	---------

Species	Rat
----------------	-----

12. Ecological Information

Ecotoxicity The product contains a substance which may have hazardous effects on the environment.

Toxicity No data available.

Ecological information on ingredients.**TIN(II) SULPHATE****Acute aquatic toxicity**

LE(C)₅₀	0.1 < L(E)C ₅₀ ≤ 1
---------------------------	-------------------------------

M factor (Acute)	1
-------------------------	---

Acute toxicity - fish	LC ₅₀ , 48 hour: 99.5 mg/l, Daphnia magna
------------------------------	--

Chronic aquatic toxicity

M factor (Chronic)	1
---------------------------	---

ETHYLENEDIAMINE

Acute toxicity - fish	, 96 hour: 115.7 mg/l, Pimephales promelas (Fat-head Minnow)
------------------------------	--

Acute toxicity - aquatic invertebrates	, 48 hour: 3 mg/l, Daphnia magna
---	----------------------------------

Acute toxicity - aquatic plants	, 96 hour: 151 mg/l, Pseudokirchneriella subcapitata
--	--

AMMONIUM SULPHATE

Acute toxicity - fish	LC ₅₀ , 53 hours: mg/l, Fish EC ₅₀ , 122-129 hours: 48 mg/l, Daphnia magna
------------------------------	---

Persistence and degradability

Persistence and degradability No data available.

Ecological information on ingredients.

TIN ALKALINE**ETHYLENEDIAMINE**

Biodegradation - 94: ~ 28 days

Bioaccumulative potential

Bio-Accumulative Potential The product does not contain any substances expected to be bioaccumulating.

Mobility in soil

Mobility The product is soluble in water.

Other adverse effects

Other adverse effects Not determined.

13. Disposal considerations**Waste treatment methods****General information**

Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.

14. Transport information**UN Number**

UN No. (TDG) 1760

UN No. (IMDG) 1760

UN No. (ICAO) 1760

UN No. (DOT) 1760

UN proper shipping name

Proper shipping name (TDG) CORROSIVE LIQUID, N.O.S. (ETHYLENEDIAMINE, TIN (II) SULPHATE)

Proper shipping name (IMDG) CORROSIVE LIQUID, N.O.S. (ETHYLENEDIAMINE, TIN (II) SULPHATE)

Proper shipping name (ICAO) CORROSIVE LIQUID, N.O.S. (ETHELENEDIAMINE, TIN (II) SULPHATE)

Proper shipping name (DOT) CORROSIVE LIQUID, N.O.S. (ETHYLENEDIAMINE, TIN (II) SULPHATE)

Transport hazard class(es)

TDG class 8

TDG label(s) 8

IMDG Class 8

ICAO class/division 8

Transport labels**Packing group**

TDG Packing Group III

IMDG packing group III

ICAO packing group III

TIN ALKALINE

DOT packing group III

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

EmS F-A, S-B

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

Ethylenediamine
10,000 lbs

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

Ammonium Tartrate
Final CERCLA RQ: 5,000 lbs
Ethylenediamine
Final CERCLA RQ: 5,000 lbs

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

Ethylenediamine
EPCRA RQ: 5,000 lbs

SARA 313 Emission Reporting

Exempt.

CAA Accidental Release Prevention

Ethylenediamine
Threshold Quantity: 20,000 lbs

SARA (311/312) Hazard Categories

Acute
Chronic

OSHA Highly Hazardous Chemicals

Exempt.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

Exempt.

California Directors List of Hazardous Substances

Ethylenediamine

Inventories

US - TSCA

All ingredients are present.

16. Other information

TIN ALKALINE

Classification abbreviations and acronyms	Acute Tox. = Acute toxicity Carc. = Carcinogenicity Eye Dam. = Serious eye damage Eye Irrit. = Eye irritation Flam. Liq. = Flammable liquid Muta. = Germ cell mutagenicity Repr. = Reproductive toxicity Resp. Sens. = Respiratory sensitisation Skin Corr. = Skin corrosion Skin Irrit. = Skin irritation Skin Sens. = Skin sensitisation STOT RE = Specific target organ toxicity-repeated exposure STOT SE = Specific target organ toxicity-single exposure
Revision date	8/14/2017
Revision	2
Hazard statements in full	H226 Flammable liquid and vapor. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H341 Suspected of causing genetic defects. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.
NFPA - instability hazard	Normally stable. (0)
NFPA - health hazard	Temporary incapacitation, injury. (2)
NFPA - flammability hazard	Will not burn. (0)

The Information in this data sheet is believed to be correct but neither we nor our employees or agents give any warranty or make any representation to the accuracy thereof and accept no liability for any loss, injury or damage which may result in it's use. The sole purpose of this data sheet is to provide guidance on the safe handling and use of the products to which it relates. It does not form part of any product specification nor part of any contract. It is not practical for the guidance and information in this data sheet to cover every conceivable application of a product and as we may not be aware of the use to which the products covered by this data sheet are to be put it remains the responsibility of the user to conduct it's own tests and to satisfy itself as to the suitability of the product.