

SAFETY DATA SHEET NICKEL-TUNGSTEN D

1. Identification

Product identifier

Product name NICKEL-TUNGSTEN D

Product number 5710

Recommended use of the chemical and restrictions on use

Application Industrial Use

Details of the supplier of the safety data sheet

Supplier SIFCO Applied Surface Concepts

5708 E. Schaaf Road Independence, Ohio 44131

U.S.A.

Tel.: +1 216-524-0099 Fax: +1 216-524-6331 E-Mail: info@sifcoasc.com

Emergency telephone number

Emergency telephone CHEMTREC (United States) (800) 424-9300; CHEMTREC (International) +1 703-527-3887

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Skin Corr. 1A - H314 Eye Dam. 1 - H318 Resp. Sens. 1 - H334 Skin Sens. 1 - H317 Muta. 2 -

H341 Carc. 1A - H350 Repr. 1B - H360FD STOT RE 1 - H372

Environmental hazards Aquatic Chronic 2 - H411

Label elements

Pictogram







Signal word

Danger

Hazard statements H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H360FD May damage fertility. May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

NICKEL-TUNGSTEN D

Precautionary statements P260 Do not breathe vapor/ spray.

P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/ container in accordance with national regulations. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P301+P310 If swallowed: Immediately call a poison center/ doctor.

Contains NICKEL SULPHATE, 1.2%

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

NICKEL SULPHATE 5-10%

CAS number: 7786-81-4

M factor (Acute) = 1 M factor (Chronic) = 1

Classification

Acute Tox. 4 - H302

Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Resp. Sens. 1 - H334 Skin Sens. 1 - H317 Muta. 2 - H341 Carc. 1A - H350i Repr. 1B - H360D STOT RE 1 - H372 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

CITRIC ACID 1-5%

CAS number: 77-92-9

Classification

Eye Irrit. 2 - H319

ACETIC ACID 1.2%

CAS number: 64-19-7

Classification

Flam. Liq. 3 - H226 Skin Corr. 1A - H314 Eye Dam. 1 - H318

NICKEL-TUNGSTEN D

SODIUM TUNGSTATE <1%

CAS number: 10213-10-2

Classification
Acute Tox. 4 - H302

BORIC ACID <1%

CAS number: 10043-35-3

Classification Repr. 1B - H360FD

2-FORMYLBENZENESULFONIC ACID SODIUM SALT <1%

CAS number: 1008-72-6

Classification
Not Classified

BENZENESULPHONAMIDE <1%

CAS number: 98-10-2

Classification

Acute Tox. 4 - H302

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Never give anything by mouth to an unconscious person. Get medical attention.

Ingestion Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical

attention immediately.

Skin Contact Remove contaminated clothing immediately and wash skin with soap and water. Continue to

rinse for at least 15 minutes and get medical attention.

Eye contact Remove affected person from source of contamination. Rinse immediately with plenty of

water. Continue to rinse for at least 15 minutes and get medical attention.

Most important symptoms and effects, both acute and delayed

Inhalation May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing, chest

tightness, feeling of chest pressure.

Ingestion May cause chemical burns in mouth and throat. May cause stomach pain or vomiting.

Skin contact May cause serious chemical burns to the skin. May cause an allergic skin reaction.

Eye contact Causes severe burns. May cause serious eye damage.

Indication of immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

5. Fire-fighting measures

NICKEL-TUNGSTEN D

Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

Special hazards arising from the substance or mixture

Specific hazards Toxic and corrosive gases or vapors.

Advice for firefighters

Protective actions during

firefighting

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

Special protective equipment

for firefighters

Use protective equipment appropriate for surrounding materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of

vapors. Provide adequate general and local exhaust ventilation.

Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Inform the relevant

authorities if environmental pollution occurs (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,

clothing or apron, as appropriate. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses. Collect and dispose of spillage as

indicated in Section 13. Wash thoroughly after dealing with a spillage.

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. See Section 11

for additional information on health hazards. See Section 12 for additional information on

ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Avoid inhalation of vapors and spray/mists.

Provide adequate general and local exhaust ventilation.

Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Protect from

freezing and direct sunlight.

Storage class Toxic storage. Corrosive storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

NICKEL SULPHATE

Long-term exposure limit (8-hour TWA): ACGIH 0.1 mg/m³

as Ni

A4

NICKEL-TUNGSTEN D

ACETIC ACID 1.2%

Long-term exposure limit (8-hour TWA): OSHA 10 ppm 25 mg/m³ Long-term exposure limit (8-hour TWA): ACGIH 10 ppm 25 mg/m³ Short-term exposure limit (15-minute): ACGIH 15 ppm 37 mg/m³

BORIC ACID

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ inhalable fraction Short-term exposure limit (15-minute): ACGIH 6 mg/m³ inhalable fraction

Α4

ACGIH = American Conference of Governmental Industrial Hygienists. OSHA = Occupational Safety and Health Administration. A4 = Not Classifiable as a Human Carcinogen.

Exposure controls

Protective equipment







Appropriate engineering

controls

As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapor or mist.

Eye/face protection Tight-fitting safety glasses.

specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. It is

recommended that gloves are made of the following material: Nitrile rubber.

Other skin and body

protection

Appropriate footwear and additional protective clothing complying with an approved standard

should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures Do not eat, drink or smoke when using this product. Wash at the end of each work shift and

before eating, smoking and using the toilet.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory

protection must be used if the airborne contamination exceeds the recommended

occupational exposure limit.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Liquid.

Color Green.

Odor No characteristic odor.

pH pH (concentrated solution): 0.8-2.0

Relative density 1.12-1.14 @ 20°C

Other information Not available.

Volatile organic compound This product contains a maximum VOC content of ACETIC ACID 14 g/l.

10. Stability and reactivity

ReactivityThere are no known reactivity hazards associated with this product.

NICKEL-TUNGSTEN D

Stability Stable at normal ambient temperatures and when used as recommended.

Possibility of hazardous

reactions

Not determined.

Conditions to avoid Avoid excessive heat for prolonged periods of time.

Materials to avoid Strong alkalis.

Hazardous decomposition

products

None at ambient temperatures.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 5,494.51

Acute toxicity - inhalation

ATE inhalation (dusts/mists

mg/l)

27.25

Inhalation May cause respiratory system irritation. May cause sensitisation by inhalation. Toxic: danger

of serious damage to health by prolonged exposure through inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected to increase risk of cancer.

Ingestion Ingestion may cause severe irritation of the mouth, the esophagus and the gastrointestinal

tract. May cause irritation. Symptoms following overexposure may include the following:

Stomach pain. Nausea, vomiting. Diarrhea.

Skin Contact Causes burns. May cause sensitisation by skin contact. May cause an allergic skin reaction.

Eye contact Causes burns. Risk of serious damage to eyes.

Acute and chronic health

hazards

Causes severe burns. May cause cancer.

Route of entry Ingestion Inhalation Skin and/or eye contact

Toxicological information on ingredients.

NICKEL SULPHATE

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

361.9

Species Rat

ATE oral (mg/kg) 500.0

Acute toxicity - inhalation

Acute toxicity inhalation 2.48

(LC₅₀ dust/mist mg/l)

Species Rat

ATE inhalation 2.48

(dusts/mists mg/l)

NICKEL-TUNGSTEN D

CITRIC ACID

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

11,700.0

Rabbit **Species**

ACETIC ACID 1.2%

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

3,310.0

Species

Rat 3,310.0

Acute toxicity - dermal

ATE oral (mg/kg)

Acute toxicity dermal (LD₅₀ 1,060.0

mg/kg)

Species Rabbit

SODIUM TUNGSTATE

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

1.19

Species Rat

ATE oral (mg/kg) 500.0

Acute toxicity - inhalation

Acute toxicity inhalation

(LC50 dust/mist mg/l)

Rat

5.01

ATE inhalation 5.01

(dusts/mists mg/l)

BORIC ACID

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

Species

4,100.0

Species

Rat

Reproductive toxicity

Reproductive toxicity -

Suspected of damaging fertility.

fertility

BENZENESULPHONAMIDE

Acute toxicity - oral

NICKEL-TUNGSTEN D

Acute toxicity oral (LD50

mg/kg)

991.0

Species Rat

ATE oral (mg/kg) 500.0

12. Ecological Information

Ecotoxicity Dangerous for the environment. May cause long-term adverse effects in the aquatic

environment.

Toxicity No data available.

Ecological information on ingredients.

NICKEL SULPHATE

Acute aquatic toxicity

LE(C)₅₀ $0.1 < L(E)C50 \le 1$

M factor (Acute) 1

Chronic aquatic toxicity

M factor (Chronic) 1

CITRIC ACID

Acute toxicity - fish LC₅₀, 96 hour: 440-706 mg/l, Carassius auratus (Goldfish)

SODIUM TUNGSTATE

Acute toxicity - fish , 48 hour: 89.4 mg/l, Daphnia magna

BORIC ACID

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 133 mg/l, Daphnia magna

BENZENESULPHONAMIDE

Acute toxicity - EC₅₀, 217 : 5 mg/l,

microorganisms EC₅₀, 243 minutes: 30 mg/l,

EC₅₀, 15 minutes: 249 mg/l,

Persistence and degradability

Persistence and degradability No data available.

Bioaccumulative potential

Bio-Accumulative Potential The product does not contain any substances expected to be bioaccumulating.

Mobility in soil

Mobility The product is soluble in water.

Other adverse effects

Other adverse effects Not determined.

NICKEL-TUNGSTEN D

13. Disposal considerations

Waste treatment methods

General information Disposal of this product, process solutions, residues and by-products should at all times

comply with the requirements of environmental protection and waste disposal legislation and

any local authority requirements.

14. Transport information

UN Number

UN No. (TDG) 1760 UN No. (IMDG) 1760 UN No. (ICAO) 1760 UN No. (DOT) 1760

UN proper shipping name

Proper shipping name (TDG) CORROSIVE LIQUID, N.O.S. (ACETIC ACID, NICKEL SULPHATE)

Proper shipping name (IMDG) CORROSIVE LIQUID, N.O.S. (ACETIC ACID, NICKEL SULPHATE)

Proper shipping name (ICAO) CORROSIVE LIQUID, N.O.S. (ACETIC ACID, NICKEL SULPHATE)

Proper shipping name (DOT) CORROSIVE LIQUID, N.O.S. (ACETIC ACID, NICKEL SULPHATE)

Transport hazard class(es)

TDG class 8
TDG label(s) 8
IMDG Class 8
ICAO class/division 8

Transport labels



Packing group

TDG Packing Group III
IMDG packing group III
ICAO packing group III
DOT packing group III

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

EmS F-A, S-B

Transport in bulk according to No information required.

Annex II of MARPOL 73/78

and the IBC Code

NICKEL-TUNGSTEN D

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

Exempt

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

Acetic Acid

Final CERCLA RQ: 5,000 lbs Nickel Sulphate Final CERCLA RQ: 100 lbs

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

Exempt.

SARA 313 Emission Reporting

Nickel Sulphate

CAA Accidental Release Prevention

HAP

Nickel Sulphate

SARA (311/312) Hazard Categories

Acute Chronic

OSHA Highly Hazardous Chemicals

Exempt.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

Nickel Sulphate

California Directors List of Hazardous Substances

Acetic Acid Nickel Sulphate

Inventories

US-TSCA

All ingredients are present.

16. Other information

Classification abbreviations

and acronyms

Acute Tox. = Acute toxicity Carc. = Carcinogenicity

Eye Dam. = Serious eye damage

Eye Irrit. = Eye irritation Flam. Liq. = Flammable liquid Muta. = Germ cell mutagenicity Repr. = Reproductive toxicity

Resp. Sens. = Respiratory sensitisation

Skin Corr. = Skin corrosion Skin Irrit. = Skin irritation Skin Sens. = Skin sensitisation

STOT RE = Specific target organ toxicity-repeated exposure STOT SE = Specific target organ toxicity-single exposure

Revision date 8/10/2017

NICKEL-TUNGSTEN D

Revision 2

Hazard statements in full H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H350i May cause cancer by inhalation. H360D May damage the unborn child.

H360FD May damage fertility. May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

NFPA - instability hazard Normally stable. (0)

NFPA - health hazard Temporary incapacitation, injury. (2)

NFPA - flammability hazard Will not burn. (0)

The Information in this data sheet is believed to be correct but neither we nor our employees or agents give any warranty or make any representation to the accuracy thereof and accept no liability for any loss, injury or damage which may result in it's use. The sole purpose of this data sheet is to provide guidance on the safe handling and use of the products to which it relates. It does not form part of any product specification nor part of any contract. It is not practical for the guidance and information in this data sheet to cover every conceivable application of a product and as we may not be aware of the use to which the products covered by this data sheet are to be put it remains the responsibility of the user to conduct it's own tests and to satisy itself as to the suitability of the product.